

32 216

ESSENCE

SINGLE HOLE SINGLE-HANDLE S-SIZE BATHROOM FAUCET 1.2 GPM

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- GROHE QuickFix® Plus installation
- 6 7/8" Faucet height
- 3 11/16" Spout reach
- 4 3/8" Aerator height
- High temperature limit stop
- Solid brass body
- 23 1/2" Nylon braided flex hoses
- CALGreen/CEC compliant
- 1.2gpm (WaterSense)



PRODUCT FEATURES:

-  GROHE StarLight®
-  GROHE SilkMove®
-  GROHE QuickFix®

CERTIFICATIONS:



- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

AVAILABLE FINISHES:

- 3221600A**  GROHE StarLight® Chrome
- 32216A0A**  Hard Graphite
- 32216BEA**  Polished Nickel InfinityFinish™
- 32216ENA**  Brushed Nickel InfinityFinish™
- 32216GNA**  Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 12-06-2021

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

32 216

ESSENCE

Pure Freude
an Wasser



SINGLE HOLE SINGLE-HANDLE S-SIZE BATHROOM FAUCET 1.2 GPM

TECHNICAL DATA:

| | |
|-------------------------------------|-------------------------|
| Product Height | 8-3/16 in |
| Product Length | 5-5/16 in |
| Product Width | 1-7/8 in |
| Fitting Spout Height | 4-3/8 in |
| Fitting Spout Reach | 3-11/16 in |
| Fitting Handle Height | 6-7/8 in |
| GPM (Min)-GPM (Max) | 1.5 gal (US)/min |
| Fitting No of Holes Required | 1 |

