30 378 **DEFINED**[™]

SINGLE-HANDLE PULL DOWN DUAL SPRAY BAR FAUCET 6.6 L/MIN (1.75 GPM)

STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight[®]
- Pull-down dual spray with toggle function: switches between regular water flow and spray without turning off the water
- 14 5/8" Faucet height
- 8 7/16" Aerator height
- 7 5/16" Faucet reach
- SpeedClean[®] anti-lime system
- · Forward rotation lever does not hit backsplash

PRODUCT FEATURES:

GROHE SilkMove®

🐨 GROHE StarLight®

👩 Speed Clean®

- 360° Swivel radius
- Solid brass body
- Flexible connection hoses
- 6.6 L/min (1.75 gpm) flow rate
- CALGreen compliant

CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 372
- CSA B125.1
- ASME A112.18.1
- · Complies with lead plumbing laws

AVAILABLE FINISHES:

30378000

GROHE StarLight® Chrome

30378DC0

SuperSteel InfinityFinish[™]

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.888.644.7643 Fax: 1.905.366.2071 We reserve the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to www.grohe.ca. 09-21-2021



Pure Freude an Wasser









30 378 DEFINED[™] SINGLE-HANDLE PULL DOWN DUAL SPRAY BAR FAUCET

6.6 L/MIN (1.75 GPM)

TECHNICAL DATA:

Product Height	14-5/8 in
Product Width	5-1/16 in
Fitting Spout Height	8-7/16 in
Fitting Spout Reach	7-5/16 in
GPM (Min)-GPM (Max)	6.6 L/min (1.75 gpm)

7⁵/_{16"} (186) $\underset{(94)}{3^{11}\!\!\!/_{16"}}$ **14**⁵/8" (371) 45° 8⁷/16" (214) <u>Ø2³/8"</u> (Ø60) V ď <u>max 1% "</u> (max 40) I ₽

册

Pure Freude an Wasser

