

30 213

PARKFIELD®

SINGLE-HANDLE PULL DOWN KITCHEN FAUCET DUAL SPRAY 1.75 GPM

*Pure Freude
an Wasser*



STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- Speed Clean® anti-lime system
- 14 3/4" Faucet height
- 7 11/16" Aerator height
- 8 5/16" Faucet reach
- 360° Swivel radius
- Single hole installation
- Single handle operation
- Forward rotating lever to prevent backsplash interference
- Dual spray with toggle function: switches between regular water flow and spray without turning off the water
- 360° Ball-joint on hose for flexible handling of spray head
- Weight operated pull back mechanism for hose
- Stainless steel braided hose
- Stainless steel braided supply lines
- Quick-Installation coupling
- 1.75gpm
- CALGreen compliant
- Compatible with GROHE Foot Control retro-fit set (30 310 000)



PRODUCT FEATURES:



-  **GROHE StarLight®**
-  **GROHE SilkMove®**
-  **Speed Clean®**

CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

AVAILABLE FINISHES:

- 30213001**  GROHE StarLight® Chrome
- 30213DC1**  SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 12-06-2021

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF LIXIL

30 213

PARKFIELD®

SINGLE-HANDLE PULL DOWN KITCHEN
FAUCET DUAL SPRAY 1.75 GPM

*Pure Freude
an Wasser*



TECHNICAL DATA:

| | |
|------------------------------|-------------------|
| Product Height | 14-3/4 in |
| Product Width | 6-9/16 in |
| Fitting Spout Height | 7-11/16 in |
| Fitting Spout Reach | 8-5/16 in |
| GPM (Min)-GPM (Max) | 1.75 gal (US)/min |
| Fitting No of Holes Required | 1 |

