

30 205

## GROHE ZEDRA

SINGLE-HANDLE PULL DOWN KITCHEN  
FAUCET TRIPLE SPRAY 6.6 L/MIN  
(1.75 GPM) WITH TOUCH TECHNOLOGY

Pure Freude  
an Wasser






### STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- 16" Faucet height
- 8 9/16" Aerator height
- 9 3/16" Faucet reach
- Touch activation of water via skin contact
- 6 V lithium-battery supply (type CR-P2)
- CE approved and meets the requirements of IAPMO IGC 349-2017
- Automatic safety stop after 60 sec. (factory set)
- Pull-down spray with 3 spray types: laminar spray, shower spray, and blade spray (reduced water consumption by up to 50% and even stronger spray performance)
- Stop function - pause button to stop the water flow
- Automatic return to laminar spray
- Adjustable flow rate limiter
- 360° Swivel spout
- Nylon braided flex hoses
- Quick installation system
- 6.6 L/min (1.75 gpm)
- GROHE Zedra is the new name for Ladylux L2



### PRODUCT FEATURES:



-  GROHE SilkMove®
-  GROHE StarLight®
-  GROHE QuickFix®

### CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

### AVAILABLE FINISHES:

- 30205002**  GROHE StarLight® Chrome
- 30205DC2**  SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.888.644.7643 Fax: 1.905.366.2071  
We reserve the right to make revisions without notice to product specifications.  
For the most current Specification Sheet, go to [www.grohe.ca](http://www.grohe.ca).  
08-18-2021

PART OF **LIXIL**

30 205

# GROHE ZEDRA

SINGLE-HANDLE PULL DOWN KITCHEN  
FAUCET TRIPLE SPRAY 6.6 L/MIN  
(1.75 GPM) WITH TOUCH TECHNOLOGY

Pure Freude  
an Wasser



## TECHNICAL DATA:

Product Height	16 in
Product Length	10-1/16 in
Product Width	6-5/16 in
Fitting Spout Height	8-9/16 in
Fitting Spout Reach	9-3/16 in
GPM (Min)-GPM (Max)	6.6 L/min (1.75 gpm)
Fitting No of Holes Required	1

