









Toilet wall-mounted	Dimension	Weight	Order number
washdown model, WaterSense® listed			
Colors			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)			
Variant			
♦ 1.6/0.8 gpf, cUPC® listed*	14 5/8" x 21 1/4" Inch	55.1 lb	25360992
♦1.6/0.8 gpf, cUPC® listed*	14 5/8" x 21 1/4" Inch	55.1 lb	25360992
Infobox			
* Complies with following standards: ASME A112.19.2/CSA B45 compliant, when installed with a seat height of 17" - 19" from tactuator plate required for installation			
Noise reduction gasket			Schallschutz-Set 005090
Actuator plate A1, for toilet, plastic mechanical actuation, for surface mounted installation, dual flush, mounting frame, mounting hardware included, push rods, front plate plastic	8 1/2" x 5 3/4" Inch	0.7 lb	WD5008
Toilet in-wall tank & carrier, Standard WaterSense® listed, For 2"x4" and 2"x6" wall installation, for toilets with a projection of <= 24 5/8", adjustable feet 0" - 9 1/2", SensoWash ready, mechanical front flush actuation, includes in-wall tank, markin of filling height, dual flush, insulated against condensation, Scope of delivery, HDPE wall-mounted toilet connection bend DN 90/90, PE wall-mounted toilet connection set DN 90, wall-mounted mounting rods M12, mounting hardware included, 2 bolt caps, cUPC® listed*, Load capacity = 880 lbs	f	35.3 lb	WD1022
Suitable products			
Toilet seat and cover hinges stainless steel, without slow close,	,		006371
Toilet seat and cover hinges stainless steel, removable, with slow close,			006379



DuraStyle Toilet wall-mounted & # 253609..92 / 253609..92

|< 14 5/8" Inch >|

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.