









Product Description:

GROHSAFE

Pressure Balance Rough-In Valve with Built-In Mechanical Diverter

Standard Specification:

- With built-in diverter
- Handle limit stop
- Diaphragm cartridge
- Check valves
- Built-in diverter
- Service stops
- Universal connection is 1/2" male by copper sweat
- Max Flow Rate 5.8 gpm at 45 psi (22 L/min)

Applicable Codes & Standards:

- Energy Policy Act of 1992
- ASME A112.18.1/CSA B125.1

Color:

□ 35016000

35 033

GROHSAFE™



PRESSURE BALANCE ROUGH-IN VALVE WITH BUILT-IN DIVERTER

STANDARD SPECIFICATION:

- 1/2" Universal Inlets/Outlets
- Built-in manual diverter
- Diaphragm cartridge
- Handle limit stop
- · Check valves
- Includes service stops
- 4.6gpm at 45psi



PRODUCT FEATURES:

CERTIFICATIONS:

AVAILABLE FINISHES:

35033000 No Finish

- CEC Certified
- · Massachusetts Plumbing Board Approved
- ASSE 1016

CEC

- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 01-21-2022

US

Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us.



Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



35 033

GROHSAFE[™]



PRESSURE BALANCE ROUGH-IN VALVE WITH BUILT-IN DIVERTER

TECHNICAL DATA:

Product Height 5-7/8 in

Product Length 3-3/4 in

Product Width 5-15/16 in

