# 28 417 **ROTAFLEX** 59" METAL LONGLIFE TWIST-FREE SHOWER HOSE

**STANDARD SPECIFICATION:** 

- GROHE StarLight®
- 59" Long
- Metal hose
- Tensile strength 500 N
- Pressure resistance: up to 14.5psi (16 bar)
- Heat resistance 165°F
- AntiFold bend proof
- 1/2" NPT female threads
- Rotation cone for Twist-free function
- Silicone strip prevents hand shower from turning while in body pray position



## **PRODUCT FEATURES:**

GROHE StarLight®

### **CERTIFICATIONS:**

- 6
- ADA
- Massachusetts Plumbing Board Approved
- CSA B125.1ASME A112.18.1

#### **AVAILABLE FINISHES:**



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.








# 28 417 **ROTAFLEX** 59" METAL LONGLIFE TWIST-FREE SHOWER HOSE

Pure Freude an Wasser



## **TECHNICAL DATA:**

Product Height	7/8 in
Product Length	59-1/16 in
Product Width	7/8 in



## 28 025 **ROTAFLEX** 69" METAL LONGLIFE TWIST-FREE SHOWER HOSE

#### **STANDARD SPECIFICATION:**

- GROHE StarLight®
- 69" Long
- Metal hose
- Tensile strength 500 N
- Pressure resistance: up to 14.5psi (16 bar)
- Heat resistance 165°F
- AntiFold bend proof
- 1/2" NPT female threads
- Rotation cone for Twist-free function
- Silicone strip prevents hand shower from turning while in body pray position



Pure Freude

an Wasser

#### **PRODUCT FEATURES:**



#### **CERTIFICATIONS:**



• ADA

- CSA B125.1
- ASME A112.18.1

#### **AVAILABLE FINISHES:**

28025000

GROHE StarLight® Chrome

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 12-07-2021

Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to <u>www.grohe.ca</u>.



# 28 025 **ROTAFLEX** 69" METAL LONGLIFE TWIST-FREE SHOWER HOSE

Pure Freude an Wasser



## **TECHNICAL DATA:**

Product Height	1/2 in
Product Length	1,750 mm
Product Width	1/2 in

