

**L-Cube Mirror with lighting # LC7380 / LC7380**

|< 25 5/8" Inch >|



| Mirror with lighting  | Dimension             | Weight | Order number |
|---|-----------------------|--------|--------------|
| cEGS/IAPMO®, LED lighting (4-sided), LED dimming function, 1 sensor switch bottom right, mirrors require a GFCI 110 V 60 Hz power source, flat plug will be supplied with mirror, LED (life span > 30,000 hours), LED module permanently enclosed, LED Modul 3500 Kelvin Lichtfarbe, 23 W |                       |        |              |
| <b>Colors</b>   |                       |        |              |
| <b>Variant</b>  |                       |        |              |
|   | 25 5/8" x 2 5/8" Inch |        | LC7380       |
|   | 25 5/8" x 2 5/8" Inch |        | LC7380       |
| <b>Infobox</b>  |                       |        |              |
| # LC 7379 - LC 7385 and LC 7388 are available from stock, Distance between sensor and reflecting surfaces = minimum 3", * Complies with following standards: UL 962 and CSA C22.2 No. 12-1982   |                       |        |              |

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.*