14 468 **CONCETTO™** PRESSURE BALANCE VALVE TRIM WITH CARTRIDGE

STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE SilkMove[®]
- Metal handle
- Metal trim plate with GROHE QuickFix®
- Includes pressure balance cartridge with double ceramic technology
- 5.2gpm (bottom) and 3.0gpm (top port) at 45psi (19 L/min)
- Requires GrohSafe™ 3.0 Rough-in Valve (35 110), (35 111), (35 112), (35 113), (35 114), (35 115), or (35 116) (sold separately)



Pure Frende

an Wasser

PRODUCT FEATURES:

GROHE StarLight®

GROHE SilkMove®

GROHE QuickFix®

CERTIFICATIONS:



- ADA
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-19-2023

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us. Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



14 468 **CONCETTO**[™] PRESSURE BALANCE VALVE TRIM WITH CARTRIDGE

Pure Freude an Wasser



TECHNICAL DATA:

Product Height 171 mm

Product Length 78 mm

Product Width 158 mm

