

Aquaflo

STM01B/G/GR/W

Main unit	Rated Voltage	AC120V / 60Hz	Drying device	Warm air volume	Greater than 0.2m ³ /min
	Rated Power	1240W		Warm wind temperature	Off, 30 C - 50 C (6 levels adjustment)
	Overall Unit Waterproof	IPx4		Heating power	250W
	Water Pressure Range	20.31-116.03psi		Safety device	Thermostat, Temperature fuse, leakage protection plug
Toilet	Electrical Wire	1.5M	Deodorization	Deodorization Method	Activated carbon
	Flushing Mode	Siphonic jet		Heated seat	Surface temperature
	Rough-in	12in	Heating power		40W
	Outlet outside diameter	80-95MM	Heated burning protection		Automatically drop to 30 C after 10 minutes of use
Water consumption	full flush≤1.45gal, half flush≤1.08gal	Safety device	Seating sensor, temperature sensor, temperature fuse, thermostat, leakage protection plug		
Cleaning Device	Drainage Method	Down-drain	Heated seat	Safety device	Seating sensor, temperature sensor, temperature fuse, thermostat, leakage protection plug
	Heating Mode	Instant heated			
	Heating Power	1300W			
	Water Temperature	Off, 30 C - 38 C (6 levels adjustment)			
	Cleaning flow rate	5 levels adjustment			
	Cleansing Mode	Rear wash/move wash, front wash/move wash, Pulse massage(option)			
	Spray Cleansing Location	5 levels adjustment			
	Water pressure Protector	Pressure stabilizing device automatic pressure relief device			
Anti-fouling device	Automatic nozzle, cleaning device, anti siphon device, anti backflow device, filtering device				
Safety device	Temperature fuse, water temperature sensor, grounding protection, temperature controller Over temperature protection and leakage protection plugs				

