

DuraSquare Shower Trim # DS5310013U.. / DS5310013U.. / DS5310013U..

|< 7 1/8 " >|



Shower Trim	Dimension	Weight	Order number
Number of outlets: 2, Water connection: Rough In Valve, Thermostat cartridge, Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 14.5038 - 72.519 psi, Escutcheon shape: Square			
Colors			
10 Chrome 46 Black Matte 70 Brushed Nickel			
Variant			
Chrome, 7x7 1/8 ", ADA: Yes, cUPC listed: Yes	7 1/8 "x3 1/2 "	2.183 lb	DS5310013U..
Black Matte, 7x7 1/8 ", ADA: Yes, cUPC listed: Yes	7 1/8 "x3 1/2 "	2.183 lb	DS5310013U..
Brushed Nickel, 7x7 1/8 ", ADA: Yes, cUPC listed: Yes	7 1/8 "x3 1/2 "	2.183 lb	DS5310013U..
Required accessories			
Thermostatic valve, 2 outlet Water connection: Male thread		2.094 lb	GK0900013

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.

DuraSquare Shower Trim # DS5310013U.. / DS5310013U.. / DS5310013U..

|< 7 1/8 " >|

